## MAGELLAN® 8300



## Specification

| DECODING CAPABILITY                   |                                                                                                                                                       |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1D / LINEAR CODES                     | Autodiscriminates all standard 1D codes including GS1 Databar™<br>linear codes                                                                        |
| STACKED CODES                         | GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBa<br>Stacked Omnidirectional                                                              |
| ELECTRICAL                            |                                                                                                                                                       |
| AC POWER REQUIREMENTS                 | AC Input: 100-250 VAC, 50-60 Hz<br>Power Consumption: Operating (Maximum): 8 Watts<br>Operating (Nominal): 7 Watts<br>Sleep Mode: 4 Watts             |
| ENVIRONMENTAL                         |                                                                                                                                                       |
| ESD PROTECTION (AIR DISCHARGE)        | 25 kV                                                                                                                                                 |
| HUMIDITY (NON-CONDENSING) TEMPERATURE | 5 - 95%<br>Operating: 10 to 40 °C / 50 to 104 °F                                                                                                      |
| TEMPERAL ORG                          | Storage/Transport: -40 to 70 °C / -40 to 158 °F                                                                                                       |
| INTERFACES                            | IBM 46xx; Keyboard Wedge: Scanner Only; OEM (IBM) USB; RS-232;<br>USB: Scanner Only                                                                   |
| AUXILIARY PORTS                       | EAS Port: Powered RS-232; Remote Scale Display; Scale Host                                                                                            |
| OPTIONAL FEATURES                     |                                                                                                                                                       |
| ALL-WEIGHS SCALE PLATTER              | Integrated Produce Lift Bar; Produce Rail™                                                                                                            |
| EAS FEATURES                          | Checkpoint Systems: Integrated EAS hardware will work with<br>Counterpoint IV, V, VI and VII models; Sensormatic: Good Read<br>Acknowledgement        |
| VALUE ADDED FEATURES                  | Diagnostic Reporting: Host Download                                                                                                                   |
| PHYSICAL CHARACTERISTICS              |                                                                                                                                                       |
| DIMENSIONS                            | Depth (Below Counter): 10.2 cm / 4.0 in                                                                                                               |
|                                       | Height (Above Counter): 13.0 cm / 5.1 in<br>Length: Model 8301 (Short, Scanner Only): 35.6 cm / 14.0 in                                               |
|                                       | Width: 29.2 cm / 11.5 in                                                                                                                              |
| READING PERFORMANCE                   | exchange of the                                                                                                                                       |
| MOTOR SPEED                           | 4,500 rpm                                                                                                                                             |
| READ HEIGHT<br>READ RATE (MAXIMUM)    | 15.2 cm / 6.0 in<br>3.900 lines/sec.                                                                                                                  |
| READING INDICATORS                    | Beeper (Adjustable Tone and Volume); Good Read LED                                                                                                    |
| SCAN LINES                            | 52<br>360°                                                                                                                                            |
| SCAN ZONE<br>SIDES READ               | 5 Sides                                                                                                                                               |
| SAFETY & REGULATORY                   | A 77 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5                                                                                                              |
| AGENCY APPROVALS                      | The product meets necessary safety and regulatory approvals for it intended use.  The Quick Reference Guide for this product can be referred to for a |
|                                       | complete list of certifications.                                                                                                                      |
| ENVIRONMENTAL COMPLIANCE              | Complies to EU RoHS                                                                                                                                   |
| LASER CLASSIFICATION                  | Caution Laser Radiation - Do not stare into beam; CDRH Class IIa<br>EN 60825 Class 1; IEC 60825 Class 1                                               |
| UTILITIES                             |                                                                                                                                                       |
| OPOS / JAVA POS                       | JavaPOS Utilities are available for download at no charge<br>OPOS Utilities are available for download at no charge                                   |

1-Year Factory Warranty

Specifications are subject to change without notice.

## Features

- Aggressive and ergonomic 360°
   5-sided scanning for best in class scanning performance
- Renowned Magellan brand quality and reliability
- All-Weighs Scale Platter with integrated Produce Lift Bar or Produce Rail<sup>m</sup> (Optional)
- FirstStrike advanced decoding software delivers the best performance in reading poor quality labels.
- Flash memory for easy software upgrades in the field
- Multiple interface solution supports all popular host interfaces
- Powered auxiliary RS-232 port for easy integration of a handheld scanner
- Supports G51 DataBar™ codes
- EAS compatible (Optional)
- Optional Value Added Features:
- Host Download Lowers Service
   Cost and Improves Operations
- Diagnostic Reporting For improved preventative
  maintenance
- Compatible with Mettler, Bizerba and other adaptive scales

www.scanning.datalogic.com



